

PROCLAD150™

The Professional Cladding Solution

PROCLAD150™ is the premium multi-layered laminate system, which provides a weatherproof cladding and jacketing system to insulated duct and pipe systems. The laminate has a zero perm rating to prevent moisture ingress and with increased strength and UV resistance, PROCLAD150™ provides a market leading solution. The technically advanced adhesive being solvent free for safe environmentally conscious use, is capable of being applied in wet/humid conditions at extremes of temperatures (-30C to +130C).

Product Performance Benefits

External & Internal Applications
Proven UV Resistance – 10 years+
Increased Puncture Resistance
Salt Water Resistant
Resistant To a Range Of Chemicals
Compliant for Direct Food Contact
Solvent Free Adhesive Technology
BS 476 parts 6&7: Class 'O'

Wider roll reduces material used by Up to 20%

	Value	Standard	
Product Thickness	150 microns		
Tensile Strength	> 200 Newtons	EN 527-3	
Elongation	> 60%	EN 527-3	
Water Permeability	0.00 g/m2/d	ASTM F1249 ISO 15106-2	
Puncture Resistance	>100 Newtons	DIN EN 14477	
Service Temperature	-40C to +140C		
Application Temperature	-30C to +130C		
Emissivity Value	0.03 to 0.84		
UV Testing	10 Years Plus	ASTM G 26A ISO 4892-2	

Product Range and Sizes:

Product No	Name	COLOUR	MICRON	WIDTH	LENGTH
P150S6	PROCLAD 150S	Silver	150	600mm	50m
P150S12	PROCLAD 150S	Silver	150	1200mm	50m
P150W6	PROCLAD 150W	White	150	600mm	50m
P150W12	PROCLAD 150W	White	150	1200mm	50m
P150B6	PROCLAD 150B	Black	150	600mm	50m
P150B12	PROCLAD 150B	Black	150	1200mm	50m

Installation Guidelines: ProTech Global Ltd provides detailed method statements for all its products for use in various applications. These must be referred to prior to starting work.

ProTech Global Ltd: Unit1 Moor Farm, Green Lane, Failand, Bristol, BS8 3TP, UK

Tel:+44 (0)117 298 0573 Email: sales@protechglobal.co.uk